0X Series 1.6 x 1.2 mm SMD Crystal

Feature

- AT-cut Crystal Construction
- Ultra thin Seam sealed ceramic surface mount
- Package Size：1.6 x 1.2 x 0.35 mm
- Pb-free and RoHS/Green compliant



Applications

- Audio Devices
- Portable devices
- Short-range Wireless module
- Computers, Modems, Microprocessors

Electrical Specifications

Item	Symb.	Min.	Typ.	Max.	Unit	Notes
Frequency Range	Freq.	24.000		54.000	MHz	
Oscillation Mode		Fundamental（AT-cut）				
Frequency Tolerance	△f/f			±10	ppm	at 25°C±2°C
Operating Temperature	T_use	-20		70	°C	
		-40		85	°C	
StorageTemperature Range	T_sta	-55		125	°C	
Shunt Capacitance	C0			3	pF	
Drive Level	DL		10	100	μW	
Load Capacitance	CL	6		20	pF	
Insulation Resistance	IR			500	MΩ	at DC 100V
Aging	f_age			3	ppm	1st. Year at 25°C

Frequency Stability & Operating Temperature Range


FT / Temp.	±10ppm	±15ppm	±20ppm	±30ppm
-20°C to +70°C	△	★	★	★
-40°C to +85°C		△	★	★

★：Available △：Conditional

Equivalent Series Resistance


Frequency Range	ESR(Max.)
24MHz≤ Freq. <32MHz	200 Ω
32MHz≤ Freq. <36MHz	100 Ω
36MHz≤ Freq. ≤54MHz	80 Ω

Dimensions (UNIT:mm)




Pin	Function
1	Xtal
2	GND
3	Xtal
4	GND

Solder pad layout (UNIT:mm)



Frequency Temperature Characteristics




Product Structure&Marking Information


- Product Structure



- Marking Information



Suggested Reflow Profile





Profile Feature	Sn - Pb Eutectic Assembly	Preheat / Soak
Preheat / Soak ● Temperature Min (Ts min) ● Temperature Max (Ts max) ● Time (Ts min to Ts max)	100°C 150°C 60-120 seconds	150°C 200°C 60-120 seconds
Ramp - up rate (TL to Tp)	3°C/ second max.	3°C/ second max.
Time maintained above ● Liquidous temperature (TL) ● Time (tL) maintained above TL	183°C 60-150 seconds	217°C 60-150 seconds
Peak package body temperature (Tp)	235°C	260°C
Time within 5° C of the specified classification temperature (Tp)	20 seconds	30 seconds
Ramp - down rate (Tp to TL)	6°C/ second max.	6°C/ second max.
Time 25° C to peak temperature	6 minutes max.	8 minutes max.
Suggust reflow times	**2 Times max.**	


Packaging Information

T=Tape and reel (3,000pcs/reel)









Pocket Tape Dimensions(mm)

Series	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
0X	0.25±0.05	1.85±0.1	0.45±0.1	8.0±0.3	3.5±0.1	1.45±0.1	4.0±0.1	4.0±0.1	2.0±0.1	ϕ1.5±0.1	2.0±0.2	4.0±1.0	ϕ13±0.5	ϕ60±1	ϕ180±1

Common Frequencies – MHz

0X Series				
24.000	24.305	24.576	25.000	26.000
27.000	27.120	30.000	32.000	37.400
38.400	40.000	48.000	50.000	52.000
54.000				